



X6-1000 high-speed 2D scanning platform

Product features

- Equipped with a new 500,000 global exposure scan engine
- Larger scanning window for easier reading
- Adjustable angle, flexible and easy to use
- Frequently used function buttons, easier to set up
- 5 styles of prompt sound, soft and bright LED indicator
- Rich interface, strong compatibility, support a variety of systems and cash registers

Physical parameters

Scan mode	Auto-sensing/continuous scanning
Communication interface	USB-HID keyboard, USB-COM virtual serial port, RS232 serial port
Interface type	USB TYPE-B
Prompt mode	Buzzer, LED light
How it is set up	Press the key to set and manually scan the setting code in turn
Housing material	ABS+PC
Cable standard	Straight line 1.3m
Exterior dimensions	158 mm×92mm×94mm(产品);1 70 mm×1 15 mm×115 mm(外包装)
Weight	Net weight 335g; Gross weight 345g

Performance parameters

Scan type	CMOS global exposure
Resolution	640*480
Light source	617nm red LED
Scan angle	± 60°, ±54°, 360° (left and right, front and back, turn).
Scan rate	120 times/sec
Field of view	48° (H) x 30° (V)
Printing contrast	Minimum 20%.
Decoding kind	1D: EAN13, EAN 8, UPC-A, UPC-E0, UPC-E1, Code128, Code39, Code93, Interleaved 2 of 5, Industrial 25, Matrix 2 of 5, Code11, CodeBar, MSI, RSS-14, RSS- Ltd, RSS- Exp, Standard 2 of 5, Plessey, ChinaPost 25, GS1 Composite 2D: QR Code, Data Matrix (DM), PDF417, Han Xin, Micro PDF417, Micro QRCode, MaxiCode, Aztec Code, Code16K, support mobile screen reading
Minimum resolution	4thousand

Electrical parameters

Input voltage	DC 5V±10%
Current	Working: 240 mA; Standby: 190 mA

Environment parameters

Temperature	0°C-50°C (working); -20°C~+70°C (storage).
Humidity	5%-95% non-condensing